

A Comprehensive Wind Energy Program

Department of Energy

Indiana Wind Working Group Indianapolis, IN December 3, 2010

Comprehensive Program



Research

Micro-reconfigurable wind farm with cooperative control
Urban wind farm rotor design and placement
Noise generation/propagation
New sensors for condition monitoring


Education / Training

Certificate program
New hands-on laboratory
course in wind energy
Internships (NREL, etc.)


Research Vision

Smart Wind Turbines & Farms

that can sense, predict, and control their own performance & reliability



Shape loads on the rotor for energy and reliability



Simulation Based Models

that can help engineers and owners optimize wind turbine and wind farm designs




Siting for noise, energy capture, and reliability

What is a Smart wind farm?

Can we identify & exploit interaction?

(If so, then we can optimize energy production at various sites and maximize uptime by reducing harmful loads.)



Characterizing Loads


 Consider an offshore wind farm, where wake interactions are known to cause losses ~25%.

Milborrow, 2003, Wind Engineering and Industrial Applications Barthelmie and Jensen, 2010, Wind Energy




Wind Turbine Dynamics & Control Testbed

Wind Turbine Test Stand




Data acquisition hardware



- •Southwest Windpower® Whisper 100™ (2.1m diameter)
- •1/4" honeycomb core
- •4 48" diameter axial fans


- •12V battery pack
- •Gefen® Wireless USB 2.0 transmitter
- National Instruments® cDAQ

How Do Rotors Respond?



Modal deflection shapes tell us about the distribution of loads on the rotor

Yaw Control for Loads



	0.8		Rot	tor-dyna	mic F	Respon	se	
_	0.7							deg deg
S) suc	0.6							Odeg Odeg
Flap Mag. Accelerations [g]	0.5							Odeg
	0.4							
	0.3		Tweak yaw to "shape" rotor loads					
lap!	0.2		VA	1		A		ado
_	0.1		*	1	A	1		
	0)	10	20		30	40	50
				Frequ	iency	[HZ]		

Yaw Angle (*)	Mean Voltage (V)	% Diff	
0	3.068	-	
5	3.0308	-1.23	
10	2.9309	-4.47	
20	2.5135	-18.07	
30	1.8738	-38.92	

1% change in power


40% change in blade response

What Does this Matter?




750 kW gearbox drive train tested at NREL Wind Technology Center

Modal Characteristics



Must avoid the coupling of the rotor response into the operation of the drive train

Why Blade Sensors?



Micro Reconfigurable Wind Farm




Objectives:

- Quantify aerodynamic interactions between turbines
- Investigate the effects of wind farm configuration on turbine performance & dynamic response
- Measure performance and dynamic response of each turbine to determine the influence of operating in wakes of upstream turbines

Wind Farm Specifications





Wind Turbine Specs


- Southwest Windpower
 Whisper 100 turbine
- 900 W Maximum
 Power at 28 mph
- 7 ft Rotor Diameter

Mounting Cart Specs

- 34 ft Turbine height
- •7' x 8' platform ~ 1100 lb
- Casters for repositioning
- & jacks for "permanent" operation

Wind Farm Instrumentation

Wind Velocity and Turbulence quantified Blades Produce Lift and Excited Dynamically Rotor Torque Produced and Rotation Occurs Generator Produces Electrical Power which charges Batteries Data Acquisition collects Accelerometer, Torque Sensor, Encoder, and Electrical Power and transmits it wirelessly Data Received and Logged for Entire Farm



Wind Turbine Wake Modeling


Objective: Improve the performance predictions for wind farms

- Model turbine wakes to improve power predictions
- Optimize wind farm layouts


Approach: CFD modeling to provide detailed information

- Wind farm as a system
- Wind turbine & wakes

Wind Farm: Turbines modeled as surface roughness in atmospheric boundary layer




Wind Turbine Wake Modeling



Urban Wind Farms

 Study VAWTs to better understand performance and noise in two typical urban environments.



Interdisciplinary


Rotors/fluid-structure













Reliability




Sensing













Power electronics








Noise




































Wind Power Integrative Graduate Education Research Training



R.2: Rotor, Drive Train, and Power Electronics
Design Concepts

R.3: Wind Turbine Diagnostics & Prognostics

R.4: Wind Turbine and Wind Farm Operation & Control


R.5: Reliability, Economic, and Ecological Simulation

R.6: Decision-Based Design Optimization

Atmospheric Science
Statistics
Computer Science
Fluid and Solid Mechanics
Electromagnetism
Control
Economics
Environmental Science



Discavery Park




Land Value

- Wind Turbine Economics and Values
 - The Contract Defines the Landowner's Economic Value, i.e. Residual value to land
 - Income and tax stream
 - Decommissioning costs
- Other Critical "Values"
 - Nuisance noise, NIMBY, visual
 - Environmental habitat, wildlife
- These "Values" extremely difficult to determine, but are important.
 - Communities often make decisions on perception of these "Values"

A Step Change in Wind

The single most important thing we can do at the university to advance wind power is to train our students on relevant projects.

NREL, GE 1.6MW turbine



NREL, Gearbox Reliability Collaborative





A Comprehensive Wind Energy Program

Department of Energy

Indiana Wind Working Group
Indianapolis, IN
December 3, 2010